



STABILITY

# FITOClima WALK-IN STABILITY



TEMPERATURE AND HUMIDITY STABILITY STORAGE ROOMS  
ENVIRONMENTAL ROOMS FOR STABILITY STUDIES, SHELF-LIFE AND PACKAGE TESTING



ICH, GMP, WHO, FDA COMPLIANT





Common applications include:

**ICH Stability Testing**  
**Pharmaceuticals**  
**Food and Beverages**  
**Cosmetics**  
**Veterinary**  
**Storage and Conservation**  
**Quality control and Research**

FitoClima Stability rooms provide the environmental control and storage flexibility to meet the evolving needs of customers throughout the years.



## ARALAB

Aralab is a company specialized in designing, developing, manufacturing and servicing of high quality climatic chambers and controlled environment rooms.

Since 1985 we have been perfecting ways to create and control temperature, humidity, light, pressure, wind and many other environmental conditions so customers and partners worldwide can have access to the best equipment for their research and testing purposes.

Aralab. Your own climate.














Certified ISO:9001 for its Quality Management System

## KEY FEATURES

- Environmental conditions controlled with consistent precision through the years
- Pre-configured with shelves designed to provide an efficient use of the internal volume
- Adaptive future proof design, with height adjustable trays and shelves that are easy to insert or remove depending on storage needs
- Content protection features, with configurable high / low temperature and humidity alarms and automatic remote notifications
- FDA 21 CFR part 11 compliant software
- Compliant and recognized by ICH, FDA, GMP and other leading industry standards
- IQ, OQ, PQ and ISO calibration documents




## TECHNICAL SPECIFICATIONS

### FITOClima WALK-IN STABILITY CHAMBERS

 TEMPERATURE RANGE <sup>[1]</sup>	15°C to 45°C						
 TEMPERATURE PRECISION	± 0,5°C						
 TEMPERATURE UNIFORMITY	± 1,0°C						
 HUMIDITY RANGE	35 to 90% RH						
 HUMIDITY PRECISION	± 1% RH						
 HUMIDITY UNIFORMITY	± 2% RH						
 SHELVES <sup>[2]</sup>	Shelves with 5 levels each. Anodized aluminium structures with polyethylene trays. Storage capacity will vary with final implementation layout and number of levels on each rack						
 APPROXIMATE STORAGE CAPACITY <sup>[3]</sup>	<table border="0"> <tr> <td>FitoClima 5.000 PH</td> <td>10 m<sup>2</sup></td> </tr> <tr> <td>FitoClima 12.000 PH</td> <td>19,5 m<sup>2</sup></td> </tr> <tr> <td>FitoClima 25.000 PH</td> <td>32 m<sup>2</sup></td> </tr> </table>	FitoClima 5.000 PH	10 m <sup>2</sup>	FitoClima 12.000 PH	19,5 m <sup>2</sup>	FitoClima 25.000 PH	32 m <sup>2</sup>
FitoClima 5.000 PH	10 m <sup>2</sup>						
FitoClima 12.000 PH	19,5 m <sup>2</sup>						
FitoClima 25.000 PH	32 m <sup>2</sup>						
 LIGHT	Recessed LED lights installed at the ceiling. Light can be operated by manual switch, triggered by door opening or controller integrated (programmable)						
 AIRFLOW VELOCITY	Can be adjusted by set-point % on the controller						
 INTERNAL VOLUMES <sup>[4]</sup>	Ranging from 5.000 to 25.000 liters						



### INSTALLATION REQUIREMENTS

 WATER	Distilled or demineralized water. 1 to 6 bar pressure and ≤ 10µ siemens conductivity.
 WATER DRAIN	Advisable: located at floor level and near the equipment, with a minimum inclination of 10° from chamber to drain
 ELECTRICAL CONNECTION	3/N/PE AC 400V ± 10%; 50Hz

[1] Temperature range extension available from 5°C to 45°C. Please contact Aralab for other technical requirements

[2] Aralab Stability rooms are pre-configured with shelves to provide the most efficient use of the available space (5 levels with approximately 470mm or 530mm of depth each, depending on chamber model). Also available stainless steel AISI 304 shelves as option.


[3] Additional trays/levels can be added to shelving configuration.

[4] Other volumes available. Please consult Aralab for bespoke rooms and special requirements

## DIMENSIONS AND DRAWINGS

### FITOCLIMA 5.000 PH

	<b>EXTERNAL DIMENSIONS</b> (H x W x D) (mm)	2.610 x 2.225 x 2.715
	<b>INTERNAL DIMENSIONS</b> (H x W x D) (mm)	2.040 x 2.010 x 1.610



- Standard refrigeration system is air cooled
- Services installation needs:
  - ½" demineralized water supply
  - 50mm water drain at floor level
- Electrical cabinet installation needs:
  - Supply power: 400VAC, 50Hz, 16A / 3-Phase + Neutral + Ground  
Electrical protection: Circuit breaker 3 x 16A + N with 300mA differential 3-Phase electrical cable RV-K 5G2.5 on the top
  - RJ45 Ethernet socket communication port on the top

FITOCLIMA 12.000 PH



**EXTERNAL DIMENSIONS**  
(H x W x D) (mm)

2.610 x 2.225 x 4.320




**INTERNAL DIMENSIONS**  
(H x W x D) (mm)

2.040 x 2.010 x 3.210




FRONT VIEW

Evaporator  
Humidifier ring  
Visiting light  
Passthrough connection (Ø80mm)  
Electrical cabinet and control panel




SECTION A-A





PLANT VIEW

Refrigeration pipeline  
Electrical cabinet and control panel



Condensing unit  
Should be installed in the exterior sheltered from sun exposure



- Standard refrigeration system is air cooled
- Services installation needs:
  - ½" demineralized water supply
  - 50mm water drain at floor level
- Electrical cabinet installation needs:
  - Supply power: 400VAC, 50Hz, 16A / 3-Phase + Neutral + Ground  
Electrical protection: Circuit breaker 3 x 16A + N with 300mA differential  
3-Phase electrical cable RV-K 5G2. on the top
  - RJ45 Ethernet socket communication port on the top

FITOCLIMA 25.000 PH



**EXTERNAL DIMENSIONS**  
(H x W x D) (mm)

2.610 x 3.825 x 4.320




**INTERNAL DIMENSIONS**  
(H x W x D) (mm)


2.040 x 3.610 x 3.210



FRONT VIEW




SECTION A-A



PLANT VIEW


Refrigeration pipeline

Electrical cabinet and control panel



1. Standard refrigeration system is air cooled
2. Services installation needs:
  - 1/2" demineralized water supply
  - 50mm water drain at floor level
3. Electrical cabinet installation needs:
  - Supply power: 400VAC, 50Hz, 16A / 3-Phase + Neutral + Ground  
Electrical protection: Circuit breaker 3 x 16A + N with 300mA differential 3-Phase electrical cable RV-K 5G2.5 on the top
  - RJ45 Ethernet socket communication port on the top

Condensing unit  
Should be installed in the exterior sheltered from sun exposure



## EQUIPMENT DESCRIPTION

### CONSTRUCTION

- Exterior: EN 14509 sandwich type high density injected polyurethane foam modular panels, 80 mm thick (other thicknesses available for different specific insulation requirements) with galvanized steel in light gray plastic finish. CFC-free.
- Walls: Galvanized steel with white epoxy paint
- Shelving and trays: standard in anodized aluminium structures with polyethylene trays (5 tiers); optional in highly resistant stainless steel
- Floor: high load capacity finish plywood with slip and wear resistant surface
- 80mm Ø entry-port
- New generation multi-color touch-screen ClimaPlus© controller
- Door with double gasket, key lock and safety opening mechanism from the inside
- Open door alarm with configurable time-out function
- Free slots for connecting and integrating external devices with the

### CLIMATIC CONTROL

- Air based, CFC free, mechanical refrigeration by hermetic condenser group
- Dual heating technology with hot gas by-pass and stainless steel electric heaters
- Humidification by ultrasonic generator with automatic water level control and self-cleaning function
- Dehumidification by condensation on the cooling system evaporator

### AIR FLOW

- Dynamic airflow with EC (variable) blower
- Forced in horizontal and downward direction
- Horizontal laminar airflow across the shelves to assure uniformity to all storage area
- Air renovation through adjustable lateral port-holes
- Airflow velocity adjustable at the ClimaPlus© controller


### CONTENT PROTECTION AND AUTOMATIC DIAGNOSTICS

- Independent thermostats for maximum and minimum temperature limits
- Automatic cut-off function, in case of excessive heating or cooling
- Configurable maximum and minimum temperature and humidity limits
- Visual and audible alarms for temperature and humidity limits
- Synoptic diagram function: a self-diagnostics tool that checks all active components of the system allowing for faster procedures and minimizing any possible downtimes



## CLIMAPLUS CONTROLLER



- Programmable Logic Controller exclusively developed by Aralab for FitoClima chambers
- Easy to use touch-screen interface
- 168mm x 112mm multicolor display
- Controls every environmental variable available for any specific FitoClima model (Temperature, Humidity, Lights, Airflow, CO<sub>2</sub>, O<sub>2</sub> and connected external devices)
- Friendly program editor for creating 32 programs of 24 segments each, allowing the design of complex and comprehensive climatic simulation programs
- Password protection of the controller functions
- Content and research protection feature, with configurable High and Low Temperature and Humidity alarms and automatic notifications
- Managing, monitoring and recording of all alarms
- Non-volatile memory, allowing the automatic restart of previously defined set-points or on-going programs due to power failure, without losing data
- Real-time monitoring of all the functions and active components of the equipment, allowing for a fast and accurate diagnostic in case of malfunction
- Possibility to control and program events by external commands and with external devices
- Graphical view of programs and climatic variables
- RS232/485, Ethernet and Wi-Fi for connecting computers to the controller
- ClimaPlus controller functions also available at the PC/Laptop with the FitoLog software pack







## FITOLOG SOFTWARE

The FitoLog software pack (**FDA 21 CFR part 11 compliant**) is a set of applications designed to facilitate the managing, monitoring and recording of programs and data from the FitoClima chambers. It consists of 3 applications: **FitoLog**, **FitoLogView** and **FitoProgram**.



**FitoLog:** Records and displays in real time all data and details related to the set-points, running variables and equipment behaviour. It also retrieves information about the active components of the chamber, running processes, errors, alarms and allows the configuration of periodic or alarm triggered remote notifications (by email or SMS, depending on existing connections and accessories).



**FitoLogView:** It is a working tool to process the data recorded by the FitoLog program. One can view, print and export the log contents to other file types, and analyse the data in other data management software (Excel, Star Office, Access or others).


**FitoProgram:** This application simplifies the creation of programs and its integration on the chamber ClimaPlus controller. Up to 32 programs, each with 24 segments, can be designed and linked to create detailed environmental profiles and simulations.

### Content of the chamber is secured with alarms, notifications, fast diagnostics and prompt troubleshooting:

With **FitoLog** it is possible to gather data from each of the chambers systems, which makes it a very useful tool to diagnose any necessary maintenance. This tool works as the “black box” of the equipment, giving Aralab technicians the necessary data to remotely carry out a fast and efficient diagnostic. All that is needed is a FitoLog file.

## OPTIONAL ACCESSORIES

- FitoLog® software pack for PC/Laptops, enabling data monitoring, logging (FDA 21 CFR part 11 compliant) and managing operations directly on a computer
- IQ, OQ, PQ validations and documentation
- ISO 17025 calibration
- Wireless / portable data loggers for temperature and humidity control of external areas
- Additional shelves and racks
- Shelves in AISI 304 stainless steel
- Observation window on the door
- Ethernet / Wi-Fi / Other connections for computer connection
- Additional entry port
- Extended temperature ranges
- Integrated water tank with electric pump and security valve
- Wall mounting conductivity meter, for water quality control, with assembling accessories
- 5 stage Reverse Osmosis with pre-decalcification water treatment system
- Internal electrical connection sockets



FitoLog software pack (FDA 21 CFR part 11 compliant)



Stainless steel shelving and additional shelves



Integrated water treatment systems

Item	Value	Unit	Acceptance	Result
1.1	20.0	°C	18.0 - 22.0	OK
1.2	65.0	%	60.0 - 70.0	OK
1.3	1.5	g/m³	1.0 - 2.0	OK
1.4	0.5	g/m³	0.2 - 1.0	OK
1.5	0.2	g/m³	0.1 - 0.5	OK
1.6	0.1	g/m³	0.05 - 0.2	OK
1.7	0.05	g/m³	0.02 - 0.1	OK
1.8	0.02	g/m³	0.01 - 0.05	OK
1.9	0.01	g/m³	0.005 - 0.02	OK
1.10	0.005	g/m³	0.002 - 0.01	OK
1.11	0.002	g/m³	0.001 - 0.005	OK
1.12	0.001	g/m³	0.0005 - 0.002	OK
1.13	0.0005	g/m³	0.0002 - 0.001	OK
1.14	0.0002	g/m³	0.0001 - 0.0005	OK
1.15	0.0001	g/m³	0.00005 - 0.0002	OK
1.16	0.00005	g/m³	0.00002 - 0.0001	OK
1.17	0.00002	g/m³	0.00001 - 0.00005	OK
1.18	0.00001	g/m³	0.000005 - 0.00002	OK
1.19	0.000005	g/m³	0.000002 - 0.000005	OK
1.20	0.000002	g/m³	0.000001 - 0.000002	OK

Qualification and Calibration documents

OTHER ACCESSORIES AVAILABLE. PLEASE CONSULT ARALAB FOR OTHER ITEMS

## ARALAB STABILITY - CUSTOMER APPLICATIONS

(CUSTOMER SPECIFICATIONS AND ACCESSORIES MAY RESULT IN DIFFERENT PRODUCT IMAGES)



Aralab FitoClima 25.000 PH – Pharmaceutical products long term



Stainless steel shelving with 9 racks for maximum storage capacity



Stability rooms turnkey project by Aralab



Six tier shelving in anodized aluminium with polyethylene trays



Set of 8 x FitoClima Stability Rooms at a Stability Services company



Interior of FitoClima 12.000PH running at 30°C / 75%rH

**Features and specifications are subject to change.** Aralab continuously studies ways to further develop its products to achieve better performances and overall product quality. As a result, characteristics and specifications provided in this document may be subject to changes.

**YOUR OWN CLIMATE**  
Our main goal

**Let's meet!**  
aralab@aralab.pt  
www.aralab.pt  
T: +351 219 154 960